



GRAFIK EYE PRESET LIGHTING CONTROLS



Two-Zone

A = 4.94" (123mm)
B = 4.50" (114mm)



Three-Zone

A = 6.69" (168mm)
B = 4.50" (114mm)



Four-Zone & Six-Zone

A = 8.31" (208mm)
B = 4.50" (114mm)

FEATURES

- Four preset lighting scenes can be accessed from the GRAFIK Eye Main Unit
- Additional scenes (up to sixteen total) can be accessed using an Infrared Remote Control or other accessory device
- Built-in infrared receiver works with Lutron Infrared Remote Controls (model GRX-IT or GRX-8IT). Most learnable remotes are also compatible
- Preset scenes can be temporarily adjusted at the GRAFIK Eye Main Unit at any time by the user without affecting the HomeWorks Interactive system programming
- Programmable fade rates can be set for each scene (between zero seconds and sixty minutes)
- All models can control incandescent, magnetic low-voltage, neon, cold cathode, electronic low-voltage (with interface) and fluorescent (with interface) lighting loads

NOTE: Lutron recommends that GRAFIK Eye Controls be mounted close to eye level (between 52" and 60" high)

MODEL	MAXIMUM ZONE CAPACITY	MAXIMUM UNIT CAPACITY	MOUNTS IN
Two-zone	800W/VA	1200W/VA	2-gang US switch box
Three-zone	800W/VA	1500W/VA	3-gang US switch box
Four-zone	800W/VA	2000W/VA	4-gang US switch box
Six-zone	800W/VA	2000W/VA	4-gang US switch box

GRAFIK EYE COLORS



COVER:

Opaque to match base (matte plastic colors only), or Translucent Black

BASE:

Standard Matte Plastic Colors: White, Beige, Ivory, Gray, Brown, Black, Taupe. Special order finishes: Bright Brass, Satin Brass, Antique Brass, Bright Chrome, Satin Chrome, Bright Nickel, Satin Nickel, Antique Bronze
Custom colors also available to match paint, wallcoverings, etc.

For more detailed technical information on these and other HomeWorks Interactive components, please consult the HomeWorks Interactive Technical Reference Guide.

©Lutron Electronics Co., Inc.
7200 Suter Road, Coopersburg PA 18036
Printed in U.S.A. 9/00 P/N 366-893

